



Product Number	Bearing Type	Bore Dia (d)	Outer Dia (D)	Width (B)	Dynamic Load Rating (Cr) (kN)	Static Load Rating (Cor) (kN)
5304	open	20 mm	52 mm	22.225 mm	22.5	14.6
5304ZZ	shielded	20 mm	52 mm	22.225 mm	22.5	14.6
5304-2RS	sealed	20 mm	52 mm	22.225 mm	22.5	14.6
5305	open	25 mm	62 mm	25.400mm	30.7	20.4
5305ZZ	shielded	25 mm	62 mm	25.400 mm	30.7	20.4
5305-2RS	sealed	25 mm	62 mm	25.400 mm	30.7	20.4
5306	open	30 mm	72 mm	30.160mm	41.6	29
5306ZZ	shielded	30 mm	72 mm	30.160 mm	41.6	29
5306-2RS	sealed	30 mm	72 mm	30.160 mm	41.6	29
5307	open	35 mm	80 mm	34.930mm	49.4	34.5
5307ZZ	shielded	35 mm	80 mm	34.930 mm	49.4	34.5
5307-2RS	sealed	35 mm	80 mm	34.930 mm	49.4	34.5
5308	open	40 mm	90mm	36.513mm	60.5	43
5308ZZ	shielded	40 mm	90 mm	36.513 mm	60.5	43

5308-2RS	sealed	40 mm	90 mm	36.513 mm	60.5	43
5309	open	45 mm	100 mm	39.688mm	72.8	53
5309ZZ	shielded	45 mm	100 mm	39.688 mm	72.8	53
5309-2RS	sealed	45 mm	100 mm	39.688 mm	72.8	53
5310	open	50 mm	110 mm	45.450mm	85.2	64
5310ZZ	shielded	50 mm	110 mm	45.450 mm	85.2	64
5310-2RS	sealed	50 mm	110 mm	45.450 mm	85.2	64
5311	open	55 mm	120 mm	49.213mm	106	81.5
5311ZZ	shielded	55 mm	120 mm	49.213 mm	106	81.5
5311-2RS	sealed	55 mm	120 mm	49.213 mm	106	81.5
5312	open	60 mm	130 mm	53.975mm	121	95
5312ZZ	shielded	60 mm	130 mm	53.975 mm	121	95
5312-2RS	sealed	60 mm	130 mm	53.975 mm	121	95
5313	open	65 mm	140mm	58.738mm	138	108
5313ZZ	shielded	65 mm	140 mm	58.738 mm	138	108
5313-2RS	sealed	65 mm	140 mm	58.738 mm	138	108
5314	open	70 mm	150 mm	63.500mm	153	125
5314ZZ	shielded	70 mm	150 mm	63.500 mm	153	125
5314-2RS	sealed	70 mm	150 mm	63.500 mm	153	125
5315	open	75 mm	160 mm	68.263mm	168	140
5315ZZ	shielded	75 mm	160 mm	68.263 mm	168	140
5315-2RS	sealed	75 mm	160 mm	68.263 mm	168	140
5316	open	80 mm	170 mm	68.623 mm	182	156
5316ZZ	shielded	80 mm	170 mm	68.263 mm	182	156
5316-2RS	sealed	80 mm	170 mm	68.263 mm	182	156
5317	open	85 mm	180 mm	73.025 mm	195	176
5317ZZ	shielded	85 mm	180 mm	73.025 mm	195	176
5317-2RS	sealed	85 mm	180 mm	73.025 mm	195	176
5318	open	90 mm	190 mm	73.025 mm	212	196
5318ZZ	shielded	90 mm	190 mm	73.025 mm	212	196
5318-2RS	sealed	90 mm	190 mm	73.025 mm	212	196